

Strong SUPER TROUPER[®] Long Throw

Model #7201156

“Follow with the Leader”

F E A T U R E S

- ✓ 2000 Watt Xenon Lamphouse with “Cold” Metal Reflector, 5600° K.
- ✓ Horizontal Masking Control/Masking Shutter Blades
- ✓ Manual Dimming Control
- ✓ Nichrome Steel Iris
- ✓ Spot Size and Edge Focus Controls
- ✓ Collapsible, Selectable-Height Floor Stand with adjustable Friction Controls for both Vertical and Horizontal movement
- ✓ Elapsed Hour Meter & DC Ammeter on Lamphouse Instrument Panel
- ✓ Shock Mount Eliminates Need to Remove Xenon Bulb while Transporting*
- ✓ Optional Six-Color, Self Cancelling Boomerang; Redesigned for Quick Mounting and Dismounting
- ✓ 1000 or 1600 Watt Operation available with use of optional Bulb Adapter Kit

* See Instruction Manual for Details



*The Standard by which
All Other Spotlights
are Measured*

The Strong Xenon Super Trouper is the best and most well-known follow spotlight in the entertainment industry today. The Super Trouper has set the standard for all other spotlights to follow. Its popularity has allowed Strong to develop other configurations of this famous spotlight for medium and short throw applications.



XENON SUPER TROUPER® Long Throw

XENON SUPER TROUPER Long Throw – Model #7201156 2000 W. Xenon
 Figures based on measurements at 60', 80% field coverage, with new bulb

Throw Distance		Largest (Flood) with Iris open				Small (Spot) with Iris open				Minimum Diameter Iris closed			
		Diameter		Intensity		Diameter		Intensity		Diameter		Intensity	
Feet	Metres	Feet	Metres	FC	Lux	Feet	Metres	FC	Lux	Inches	Metres	FC	Lux
100	32.8	13.8	4.5	289	3,107	6.5	2.1	1,229	13,227	20	0.51	1,229	13,227
120	39.4	16.6	5.4	200	2,157	7.8	2.6	853	9,186	24	0.61	853	9,186
150	49.2	20.7	6.8	128	1,381	9.8	3.2	546	5,879	30	0.76	546	5,879
170	55.8	23.5	7.7	100	1,075	11.1	3.6	425	4,577	34	0.86	425	4,577
200	65.6	27.6	9.1	72	777	13	4.3	307	3,307	40	1.02	307	3,307
220	72.2	30.4	10	60	642	14.3	4.7	254	2,733	44	1.12	254	2,733
250	82	34.5	11.3	46	497	16.3	5.3	197	2,116	50	1.27	197	2,116
270	88.6	37.3	12.2	40	426	17.6	5.8	169	1,814	54	1.37	169	1,814
300	98.4	41.4	13.6	32	345	19.5	6.4	137	1,470	60	1.52	137	1,470
320	105	44.2	14.5	28	303	20.8	6.8	120	1,292	64	1.63	120	1,292
350	114.8	48.3	15.8	24	254	22.8	7.5	100	1,080	70	1.78	100	1,080

SPECIFICATIONS

Letter/Description/Dimension

- A Overall length of unit 77½"
- Length of head unit (without boomerang) 71½"
- B Overall width of unit 45"
- C* Overall height of unit 62"
- D* Height of pivot point 50"
- E* Height of beam when horizontal 53"
- F Front clearance radius for vertical movement 43"
- G Front clearance radius for horizontal movement 41"
- H Rear clearance radius for vertical movement 40"
- I Rear clearance radius for horizontal movement 37"
- J Width of head unit (without boomerang) 12"
- K Width of boomerang 15"
- L Height of boomerang 18½"
- M Height of head unit 20"

XENON SUPER TROUPER Long Throw – Model #7201156 1600 W. Xenon
 Figures based on measurements at 60', 80% field coverage, with new bulb



Throw Distance		Largest (Flood) with Iris open				Small (Spot) with Iris open				Minimum Diameter Iris closed			
		Diameter		Intensity		Diameter		Intensity		Diameter		Intensity	
Feet	Metres	Feet	Metres	FC	Lux	Feet	Metres	FC	Lux	Inches	Metres	FC	Lux
70	23	9.7	3.2	494	5,318	4.5	1.5	2,059	22,159	13.7	0.35	2,059	22,159
100	32.8	13.9	4.6	242	2,606	6.4	2.1	1,009	10,858	19.6	0.5	1,009	10,858
120	39.4	16.6	5.4	168	1,809	7.7	2.5	700	7,540	23.5	0.6	700	7,540
150	49.2	20.8	6.8	108	1,158	9.6	3.1	448	4,826	29.4	0.75	448	4,826
170	55.8	23.6	7.7	84	902	10.9	3.6	349	3,757	33.3	0.85	349	3,757
200	65.6	27.7	9.1	61	651	12.9	4.2	252	2,715	39.1	0.99	252	2,715
220	72.2	30.5	10	50	538	14.1	4.6	208	2,243	43.1	1.09	208	2,243
250	82	34.6	11.4	39	417	16	5.3	161	1,737	48.9	1.24	161	1,737
310	101.6	43	14.1	25	271	19.9	6.5	105	1,130	60.7	1.54	105	1,130

Maximum height at rear with maximum downward tilt 82"
 Maximum height at front with maximum upward tilt 80"

Maximum downward tilt 45°
 Maximum upward tilt 25°
 Horizontal sweep 360°

Net weight:
 Spotlight Head & Base 279 lb.
 Boomerang 15 lb.
 Power Supply 42 lb.
 Gross weight (crated) 700 lb.
 Domestic pack shipping crate 88" x 25½" x 41½"

* Measurements shown with spotlight at lowest height. Adjustable upward in two increments of (4) inches.



Strong Entertainment Lighting
 4350 McKinley Street • Omaha NE 68112 USA
 Tel 402/453-4444 • Fax 402/453-7238
www.strong-lighting.com